



ARCOY INDUSTRIES (INDIA) PVT. LTD.

Your partners in corrosion prevention

An ISO 9001 : 2000 Company



AROPRIMER

INTRODUCTION :

AROPRIMER is a bitumen based primer, which contains volatile inflammable solvents. It is a thin black liquid. It is applied by brush over the cleaned dry concrete surface to act as a primer and to increase the bonding property between concrete and mastic membrane.

SURFACE PREPARATION :

Steel surfaces should be free from rust, scale, grease, oil, etc. Preparation can be done by wire brushing, sand or shot blasting or by chemical etching.

Concrete surfaces must be cleaned of all lubricants, previous coatings etc. If the surfaces are contaminated by acid, it has to be neutralized, washed with fresh water and allowed to become absolutely dry prior to application.

PROPERTIES :

Drying Time	: Not more than 8 hours.
Consistency	: Smooth & uniform; suitable for application by brush.
Finish	: Smooth semi-glossy.
Colour	: Black.
Flash Point	: 30°C minimum.
Shelf Life	: 12 months at Room Temperature (under shade.)
Dry Film Thickness	: 30 to 35 micron/coat.
Coverage	: Average 3 to 4m ² per ltr. per coat.

SERVICE :

The ARCOY Technical Department is maintained to provide you with assistance and advice on any problem of acid or alkali proof construction. Write to us about your service conditions to obtain prompt recommendations and design suggestions. We will be more than glad to be of assistance.

**CORROSION
NO ENTRY**

*Sturdy, Strong, Reliable,
Modern...only Arcoy*

ARCOY INDUSTRIES (INDIA) PVT. LTD.

606, Abhijeet-I, Mithakali Six Roads, Ellisbridge, Ahmedabad - 380 006. INDIA
Phone : (91) 79-26401228, 26427762, 26425300 Fax : (91) 79-26561331
E-mail : contact@arcoy.com • arcoy@icenet.co.in • Visit us at : www.arcoy.com